

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY

OF A PORTION

OF THE WEST BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS

7, 8, 9, AND 17

IN

TOWNSHIP 33 SOUTH, RANGE 23 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

*Ferrel D. Reynolds,
Cadastral Surveyor*

Under special instructions dated *July 27, 1993*, approved *July 27, 1993*, which provided for the surveys included under Group Number *807*, and assignment instructions dated *July 30, 1993*.

Survey commenced *August 16, 1993*

Survey completed *September 29, 1993*

INDEX DIAGRAM

Township 33 South, Range 23 East

		6			
6	5	4	3	2	1
15 14	14	9 5			
	14	5			
3 7	8 8	9 4	10	11	12
2 13	12	8			
	11 7				
18 10	17 6	16	15	14	13
	10				
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

The Subdivision of Section 7.....	Page 15
The Subdivision of Section 8.....	Page 16
The Subdivision of Section 9	Page 17
The Subdivision of Section 17.....	Page 19

TOWNSHIP 33 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines and the survey of the subdivision of sections 7, 8, 9 and 17, Township 33 South, Range 23 East, Salt Lake Meridian, Utah.

History of SurveysSurveyed byRetr. or Resurveyed byNORTH BOUNDARY

Portion	F. Dickert	1878		
Portion	E. Beuther	1884		
All			J.M. Lentz	1900-01
Portion			W.B. Rice	1915
All			R. Gentry	1917

SOUTH BOUNDARY

Portion	E. Beuther	1884		
All			J.M. Lentz	1900-01

EAST BOUNDARY

All	F. Dickert	1878		
All			J.M. Lentz	1900-01

WEST BOUNDARY

All	E. Buether	1884		
All			J.M. Lentz	1900-01
Portion	Remonumentation		F.D. Reynolds	1970

SUBDIVISION

All	J.M. Lentz	1900-01		
Portion	Remonumentation		F.D. Reynolds	1970

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 807, dated July 27, 1993.

The directions of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

TOWNSHIP 33 SOUTH, RANGE 23 EAST, SALT LAKE MERIDIAN, UTAH

CHAINS

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the corner of sections 9, 10, 15, and 16, as determined by using the Global Positioning System (G.P.S.), static relative positioning techniques, utilizing U.S. Coast and Geodetic Survey triangulation station "Indian 1953" is:

Latitude 37°54' 59.01" N. Longitude 109°23' 28.02" W.
N.A.D. 1927

This corner is now designated a B.L.M. control station.

Dependent Resurvey of a Portion of the West Boundary,
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by E. Buether in 1884
and the Resurvey by J. M. Lentz in 1900-01

Beginning at the corner of sections 7, 12, 13, and 18, T. 33 S., Rs. 22 and 23 E., monumented with a granite stone, 15x10x6 ins., firmly set and dimly marked with 4 notches on the S and 2 notches on the N edges, witnessed by a mound of stone W of the corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, with aluminum cap marked:

T33S
R22E R23E
S12 | S7
S13 S18
1993

Deposit the marked stone alongside the aluminum post.

Corner is located on a N slope, 86 lks. dist., N of an E and W fence line.

N. 0° 00.7' W., between sections 7 and 12.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.194

Point for the 1/4 section corner of sections 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S
R22E R23E
1/4
S12 | S7
1993

Corner is located in thick oak and serviceberry brush.

80.388

The corner of sections 1, 6, 7 and 12, monumented with a sandstone, 18x10x5 ins., firmly set and plainly marked 5 notches on the S and 1 notch on the N edges, witnessed by a mound of stone, W of the corner

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T33S
R22E R23E
S1 | S6
S12 | S7
1993

Deposit the marked stone alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
J. M. Lentz in 1900-01

From the corner of sections 9, 10, 15, and 16, as determined from the projection of a fence line from the south and at the center of road, 50 lks. wide running east and west.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T33S R23E

S9 | S10

S16 | S15

1993

This corner is now a B.L.M. control station, hereinbefore described.

Corner is located in a draw, drains N, and 25 lks. dist., S of a fence line, bears E and W.

N. $0^{\circ} 10.3'$ W., between sections 9 and 10.

Over gentle rolling mountainous land, through scattered pinon, juniper and oak brush.

39.741 The $1/4$ section corner of sections 9 and 10, monumented with a sandstone, 16x10x8 ins., firmly set and plainly marked $1/4$ on the W face.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E

 $1/4$

S9 | S10

1993

Deposit the marked stone alongside the aluminum post.

Corner is located at the corner of fences, projecting E, W and S.

N. $0^{\circ} 08.1'$ E., beginning new measurement.

20.170 Point for the N $1/16$ section corner of sections 9 and 10.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E

N $1/16$

S9 | S10

1993

The corner of fences, projecting N and W, bears N. $63^{\circ} 16'$ W., 21 lks. dist.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.340

Point for the corner of sections 3, 4, 9, and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T33S R23E

S4	S3
----	----

S9	S10
----	-----

1993

Set a steel fence post alongside the aluminum post.

Raise a mound of stone, W of the corner.

Corner is located in a draw, drains E.

From this corner, the corner of sections 2, 3, 10, and 11, monumented with a sandstone, 14x10x5 ins., firmly set and plainly marked with 2 notches on the E and 5 notches on the S edges, bears S. 89° 57.3' E., 79.720 chs. dist.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E

S3	S2
----	----

S10	S11
-----	-----

1993

Deposit the marked stone alongside the aluminum post.

This control line was fully retraced and a careful search was made for the 1/4 section corner of sections 3 and 10 which was not recovered.

N. 0° 54.0' W., between sections 3 and 4.

Over rolling mountainous land, through scattered pinon, juniper and oak brush.

40.342

Point for the 1/4 section corner of sections 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T33S R23E

1/4

S4 | S3

1993

Set a steel fence post alongside the aluminum post.

Corner is located 38 lks. dist., W of 4 strand barb wire fence, bears N and S.

80.704

The corner of sections 3 and 4, on the north boundary of the township, monumented with a sandstone, 14x8x4 ins., firmly set and plainly marked with 3 notches on the E and W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T32S R23E

S33

S4 | S3

T33S

1993

Deposit the marked stone alongside the aluminum post.

Corner is located in a fence line, bears E and W.

From the corner of sections 16, 17, 20, and 21, monumented with a mound of stone at the corner of fences, projecting S and W. No marked rock was found. This point is accepted as the best available evidence of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone to top, with aluminum cap marked:

T33S R23E

S17 | S16

S20 | S21

1993

N. 0° 47.1' E., between sections 16 and 17.

Over broken mountainous land, through pinon, juniper, oakbrush and serviceberry growth.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.288

The 1/4 section corner of sections 16 and 17, monumented with a sandstone, 17x12x5 ins., firmly set and plainly marked 1/4 17 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
1/4
S17 | S16
1993

Deposit the marked stone alongside the aluminum post.

N. 0° 43.7' W., beginning new measurement.

20.152

Point for the N 1/16 section corner of sections 16 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
N 1/16
S17 | S16
1993

40.304

The corner of sections 8, 9, 16, and 17, monumented with a sandstone, 18x10x6 ins., firmly set and plainly marked with 4 notches on the E and S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
S8 | S9
S17 | S16
1993

Deposit the marked stone alongside the aluminum post.

Corner is located at the corner of fences projecting E, W and N.

From the corner of sections 9, 10, 15, and 16.

S. 89° 53.8' W., between sections 9 and 16.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Over gentle rolling mountainous land, through pinon, juniper, oak and seviceberry brush.

39.916 Point for the 1/4 section corner of sections 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
1/4 S9
 S16
 1993

Corner is located on SE slope, in a railed area, 63 lks. dist., N of an E and W fence line.

79.832 The corner of sections 8, 9, 16, and 17.

N. 0° 09.9' W., between sections 8 and 9.

Over rolling mountainous land, through pinon, juniper, oak and seviceberry brush.

40.106 Point for the 1/4 section corner of sections 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

T33S R23E
1/4
S8 | S9
1993

80.212 The corner of sections 4, 5, 8, and 9, monumented with a sandstone, 14x10x5 ins., firmly set and plainly marked with 4 notches on the E and 5 notches on the S edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
S5 | S4
S8 | S9
1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Deposit the marked stone alongside the aluminum post.

Corner is located in dense pinon and juniper growth.

From the corner of sections 3, 4, 9, and 10.

N. 89° 56.4' W., between sections 4 and 9.

Over mountainous land, through thick pinon and juniper growth.

19.935 Point for the E 1/16 section corner of sections 4 and 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T33S R23E
E 1/16	<u>S4</u>
	S9
	1993

Corner is located on a SE slope.

39.870 The 1/4 section corner of sections 4 and 9, monumented with a sandstone, 12x10x6 ins., firmly set and dimly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T33S R23E
1/4	<u>S4</u>
	S9
	1993

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone N of the corner.

S. 89° 55.3' W., beginning new measurement.

40.152 The corner of sections 4, 5, 8, and 9.

From the corner of sections 16, 17, 20, and 21.

N. 88° 36.9' W., between sections 17 and 20.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Over mountainous land, through thick pinon, juniper, oak and serviceberry brush.

- 39.881** The 1/4 section corner of sections 17 and 20, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, with brass cap marked.

T33S R23E
1/4 S17
 S20
 1970

This corner was remonumented by F.D. Reynolds in 1970.

Corner is located in an E and W fence line.

S. 88° 37.7' W., beginning new measurement.

- 19.906** Point for the W 1/16 section corner of sections 17 and 20.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

T33S R23E
W 1/16 S17
 S20
 1993

Corner is located in an E and W fence line.

- 39.812** The corner of sections 17, 18, 19 and 20, monumented with an iron post, 2 1/2 ins. diam., 6 ins. above ground, with brass cap marked.

T33S R23E
S18 | S17
S19 | S20
1970

This corner was remonumented by F.D. Reynolds in 1970.

Corner is located at the corner of fences, projecting E and N.

N. 0° 02.8' W., between sections 17 and 18.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

- 20.101** Point for the S 1/16 section corner of sections 17 and 18.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T33S R23E
S 1/16
S18 | S17
1993

Set a steel fence post alongside the aluminum post.

Corner is located 8 lks. dist., E of a 4 strand barb wire fence line, bears N and S.

40.202 The 1/4 section corner of sections 17 and 18, monumented with an iron post, 2 1/2 ins. diam., 6 ins. above ground, with brass cap marked:

T33S R23E
1/4
S18 | S17
1970

This corner was remonumented by F.D. Reynolds in 1970.

Corner is located in a N and S fence line.

N. 0°36.7' W., beginning new measurement.

19.874 Point for the N 1/16 section corner of sections 17 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone to top, with aluminum cap marked:

T33S R23E
N 1/16
S18 | S17
1993

Corner is located 1 lk. dist., E of a 4 strand N and S fence line.

39.748 The corner of sections 7, 8, 17, and 18, monumented with an iron post, 2 1/2 ins. diam., 6 ins. above ground, with brass cap marked.

T33S R23E
S7 | S8
S18 | S17
1970

This corner was remonumented by F.D. Reynolds in 1970.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located at the corner of fences projecting N, S and W.

From the corner of sections 8, 9, 16, and 17.

S. 89° 33.1' W., between sections 8 and 17.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

20.038 Point for the E 1/16 section corner of sections 8 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

	T33S R23E
E 1/16	<u>S8</u>
	S17
	1993

Corner is located in a N and S fence line.

40.076 Point for the 1/4 section corner of sections 8 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

	T33S R23E
1/4	<u>S8</u>
	S17
	1993

Corner is located 57 lks. dist., N of an E and W fence line.

60.114 Point for the W 1/16 section corner of sections 8 and 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

	T33S R23E
W 1/16	<u>S8</u>
	S17
	1993

Corner is located in pasture land, 14 lks. dist., N of an E and W fence line.

80.152 The corner of sections 7, 8, 17, and 18.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89° 32.4' W., between sections 7 and 18.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

39.614

The 1/4 section corner of sections 7 and 18, monumented with an iron post, 2 1/2 ins. diam., 6 ins. above ground, with brass cap mkd.

T33S R23E

1/4 S7
 S18
 1970

This corner was remonumented by F.D. Reynolds in 1970.

N. 89° 53.4' W., beginning new measurement.

20.006

Point for the W 1/16 section corner of sections 7 and 18.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E

W 1/16 S7
 S18
 1993

Corner is located on a spur, projecting NE, and 37 lks. dist., N of an E and W fence line.

38.532

The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

From the corner of sections 7, 8, 17, and 18.

N. 0° 08.5' E., between sections 7 and 8.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

40.398

Point for the 1/4 section corner of sections 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

T33S R23E

1/4
S7 | S8
1993

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located 3 lks. dist., N of an old E and W fence line.

80.796

The corner of sections 5, 6, 7, and 8, monumented with a sandstone, 16x10x6 ins., firmly set and plainly marked with 5 notches on the S and E edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone to top, with aluminum cap marked:

T33S R23E

S6 | S5

S7 | S8

1993

Deposit the marked stone alongside the aluminum post.

From the corner of sections 4, 5, 8, and 9.

S. 89° 58.1' W., between sections 5 and 8.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

39.852

Point for the 1/4 section corner of sections 5 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

T33S R23E

1/4

S5

S8

1993

Corner is located 32 lks. dist., E of a N and S fence line.

79.704

The corner of sections 5, 6, 7, and 8.

S. 89° 54.0' W., between sections 6 and 7.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

39.935

The 1/4 section corner of sections 6 and 7, monumented with a sandstone, 14x10x3 ins., firmly set and plainly marked 1/4 S6 on the N face.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

T33S R23E
1/4 S6
 S7
 1993

Deposit the marked stone alongside the aluminum post.

N. 89° 55.1' W., beginning new measurement.

19.990 Point for the W 1/16 section corner of sections 6 and 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T33S R23E
W 1/16 S6
 S7
 1993

38.411 The corner of sections 1, 6, 7, and 12, on the west boundary of the township, hereinbefore described.

The Subdivision of Section 7,
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 7 and 18.

N. 0°05.5' W., on the N-S center line of section 7.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

40.177 Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
C 1/4 S7
 1993

80.407 The 1/4 section corner of sections 6 and 7.

THE SUBDIVISION OF SECTION 7,
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 7 and 8.

N. 89° 51.7' W., on the E-W center line of section 7.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

39.774 The center 1/4 section corner of section 7.

59.772 Point for the center W 1/16 section corner of section 7.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
C $\frac{W \ 1/16}{S7}$ C
1993

78.245 The 1/4 section corner of sections 7 and 12, on the west boundary of the township, hereinbefore described.

From the W 1/16 section corner of sections 7 and 18.

N. 0° 05.0' W., on the N-S center line of the SW 1/4 of section 7.

40.186 The center W 1/16 section corner of section 7.

N. 0° 05.0' W., on the N-S center line of the NW 1/4 of section 7.

40.210 The W 1/16 section corner of sections 6 and 7.

The Subdivision of Section 8,
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 8 and 17.

N. 0° 00.6' W., on the N-S center line of section 8.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

40.254 Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 8,
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T33S R23E
C 1/4 S8
1993

Corner is located on a SW slope of hill.

80.504 The 1/4 section corner of sections 5 and 8.

From the 1/4 section corner of sections 8 and 9.

S. 89° 45.5' W., on the E-W center line of section 8.

39.965 The center 1/4 section corner of section 8.

79.929 The 1/4 section corner of sections 7 and 8.

The Subdivision of Section 9,
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 9 and 16.

N. 0° 00.6' E., on the N-S center line of section 9.

Over rolling mountainous land, through pinon, juniper, oak and serviceberry brush.

39.923 Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, in a mound of stone to top, with aluminum cap marked:

T33S R23E
C 1/4 S9
1993

Set a steel fence post alongside the aluminum post.

Corner is located 95 lks. dist., S of a 4 strand fence line, bears E and W.

60.058 Point for the center N 1/16 section corner of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

THE SUBDIVISION OF SECTION 9,
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T33S R23E

C
N 1/16 | S9
C
1993

Corner is located on a SE slope.

80.193 The 1/4 section corner of sections 4 and 9.

From the 1/4 section corner of sections 9 and 10.

N. 89° 50.5' W., on the E-W center line of section 9.

19.893 Point for the center E 1/16 section corner of section 9.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
C — E 1/16 — C
S9
1993

Set a steel fence post alongside the aluminum post.

Corner is located 15 lks. dist., S of a 4 strand fence line, bears E and W.

39.786 The center 1/4 section corner of section 9.

79.820 The 1/4 section corner of sections 8 and 9.

From the center E 1/16 section corner of section 9.

N. 0° 04.3' E., on the N-S center line of the NE 1/4 of section 9.

20.152 Point for the NE 1/16 section corner of section 9, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
NE 1/16 S9
1993

THE SUBDIVISION OF SECTION 9,
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post alongside the aluminum post.

From this point, the corner of fences projecting E and S, bears N. 36° 38' W., 48.6 lks. dist.

40.304

The E 1/16 section corner of sections 4 and 9.

From the N 1/16 section corner of sections 9 and 10.

N. 89° 53.4' W., on the E-W center line of the NE 1/4 of section 9.

19.914

The NE 1/16 section corner of section 9.

39.828

The center N 1/16 section corner of section 9.

The Subdivision of Section 17,
T. 33 S., R. 23 E., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 17 and 20.

N. 0° 07.5' W., on the N-S center line of section 17.

Over mountainous land, through pinon, juniper, oak and serviceberry brush.

19.643

Point for the center S 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
C
S 1/16 | S17
C
1993

Corner is located on a SE slope.

39.286

Point for the center 1/4 section corner, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
C 1/4 S17
1993

THE SUBDIVISION OF SECTION 17,
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS**59.298**

Point for the center N 1/16 section corner.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
C
N 1/16 | S17
C
1993

79.310

The 1/4 section corner of sections 8 and 17.

From the 1/4 section corner of sections 16 and 17.

S. 89° 56.9' W., on the E-W center line of section 17.

20.251

Point for the center E 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
C — E 1/16 — C
S17
1993

40.502

The center 1/4 section corner of section 17.

60.374

Point for the center W 1/16 section corner of section 17.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone to top, with aluminum cap marked:

T33S R23E
C — W 1/16 — C
S17
1993

Set a steel fence post alongside the aluminum post.

80.246

The 1/4 section corner of sections 17 and 18.

From the center E 1/16 section corner of section 17.

N. 0° 25.7' W., on the N-S center line of the NE 1/4 of section 17.

THE SUBDIVISION OF SECTION 17,
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS**20.082**

Point for the NE 1/16 section corner of section 17, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with aluminum cap marked:

T33S R23E
NE 1/16 S17
1993

40.164

The E 1/16 section corner of sections 8 and 17.

From the N 1/16 section corner of sections 16 and 17.

S. 89° 45.1' W., on the E-W center line of the NE 1/4 of section 17.

20.144

The NE 1/16 section corner of section 17.

40.288

The center N 1/16 section corner of section 17.

From the W 1/16 section corner of sections 17 and 20.

N. 0° 05.2' W., on the N-S center line of the SW 1/4 of section 17.

19.872

Point for the SW 1/16 section corner of section 17, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with aluminum cap marked:

T33S R23E
SW 1/16 S17
1993

39.744

The center W 1/16 section corner of section 17.

From the center S 1/16 section corner of section 17.

S. 89° 17.1' W., on the E-W center line of the SW 1/4 of section 17.

19.889

The SW 1/16 section corner of section 17.

39.778

The S 1/16 section corner of sections 17 and 18.

THE SUBDIVISION OF SECTION 17,
T. 33 S., R. 23 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the center W 1/16 section corner of section 17.

N. 0°22.1' W., on the N-S center line of the NW 1/4 of section 17.

19.943

Point for the NW 1/16 section corner of section 17, at intersection with the E-W center line.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T33S R23E
NW 1/16 S17
1993

Raise a mound of stone W of the corner.

Corner is located on a NW slope in thick pinon, juniper and oak brush.

39.886

The W 1/16 section corner of sections 8 and 17.

From the center N 1/16 section corner of section 17.

S. 89° 44.8' W., on the E-W center line of the NW 1/4 of section 17.

19.955

The NW 1/16 section corner of section 17.

39.910

The N 1/16 section corner of sections 17 and 18.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Philip Tobler	Surveying Technician
Shawn Peterson	Surveying Technician


CERTIFICATE OF SURVEY

I, *Ferrel D. Reynolds, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *27th day of July, 1993*, I have *dependently resurveyed a portion of the west boundary, a portion of the subdivisional lines, and subdivided sections 7, 8, 9, and 17, in Township 33 South, Range 23 East*,

of the *Salt Lake* Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 22, 1996

Date



(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of sections 7, 8, 9, and 17, in Township 33 South, Range 23 East, Salt Lake Meridian, Utah*,

executed by *Ferrel D. Reynolds, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

May 22, 1996

Date



(Chief Cadastral Surveyor for Utah)